



LED Emergency Exit Sign Light

LCD Backlight Module And Super-thin Size

Characters:

- ▶ **Super-Thin Design** - High quality anodized aluminum alloy frame; 20-mm maximum thickness; light and elegant with attractive appearance.
- ▶ **Common light Design** - A common light for wall-hang/ Ceiling-hang/ Ceiling-suspend. Only installation of additional parts is required.
- ▶ **Fixed Voltage switching power** - Back-up power when discharged, Variation of light intensity is within 5% in 60 minutes.
- ▶ **Advanced Opt guide** - Same opt guide technology as the LCD show super high intensity and the average light intensity is above 80%.
- ▶ **High Efficiency Ni-MH Battery** - Highly efficient, long life and rechargeable for 500 times. 18-hour charging time for provision of 90-minute operation.
- ▶ **Lead in the Industry** - SMD-TYPE LED Automatic Process with a stable quality. Long life and energy-saving.
- ▶ **Alarm** - Optional Power Outage Alarm.



Customize Panels



● Specification: Operating Voltage: 90V ~ 245V

	Model No.	LED Spec	Ni-MH Battery	Size (mm)	Power Rating	Energy Consumption
Small	LE-A/ LD-A Double side: LD-AD	SMD White LED 0.07W x 18	3.6V 600mAh	365x175x20 Sign:360x120	Voltage 90V-245V Current 22mA	2.4W
Medium	LE-A2/ LD-A2 Double side:LD-A2D	SMD White LED 0.07W x 36	3.6V 1100mAh	505x225x20 Sign:500x170	Voltage 90V~245V Current 36mA	4W
Large	LE-A3/ LD-A3 Double side:LD-A3D	SMD White LED 0.07W x 36 x 2	3.6V 2200mAh	1005x255x20 Sign:1000x200	Voltage 90V~245V Current 81mA	8.9W