



# SAFE

Compliant with CNS Number 10207 of the National Standard

## LED Emergency Exit Sign Light

### LCD backlight module And flippable frame cover

#### 特色：

- ▣ **Cover open patent design** - The four sides of the frame can be opened and closed repeatedly using no tool for replacement of the sign panel, LED light bar, battery and etc. Time-saving and convenient.
- ▣ **Super-thin Design** - Aluminum alloy frame; 26-mm maximum thickness; high-quality anodizing process; light and elegant.
- ▣ **Common light Design** - A common light for wall-hang/Ceiling-hang/ Ceiling-suspend. Only installation of additional parts is required.
- ▣ **Fixed Voltage switching power** - Back-up power when discharged, Variation of light intensity is within 5% in 60 minutes.
- ▣ **Advanced Opt guide** - Same Opt guide technology as the LCD show super high intensity and the average light intensity is above 80%.
- ▣ **High Efficiency Ni-MH Battery** - Highly efficient, long life and rechargeable for 500 times. 18-hour charging time for provision of 90-minute operation.
- ▣ **Alarm** - Optional Power Outage Alarm.



#### Customize Panels



#### ● Specification: Operating Voltage: 90V ~ 245V

	Model No.	LED Spec	Ni-MH Battery	Size (mm)	Power Rating	Energy Consumption
Small	LE-N/ LD-N Double side: LD-ND	SMD White LED 0.07W x 18	3.6V 600mA	430x190x26 Sign:360x120	Voltage 90V~245V Current 22mA	2.4W
Medium	LE-N2/ LD-N2 Double side:LD-N2D	SMD White LED 0.07W x 36	3.6V 1100mA	570x240x26 Sign:500x170	Voltage 90V~245V Current 36mA	4W
Large	LE-N3/ LD-N3 Double side:LD-N3D	SMD White LED 0.07W x 36 x 2	3.6V 2200mA	1070x270x26 Sign:1000x200	Voltage 90V~245V Current 81mA	8.9W